

# Product data sheet

Specifications



APC Smart-UPS On-Line, 10kVA/  
10kW, Tower, 230V/400V, 6x  
C13+4x C19 IEC outlets, Network  
Card+SmartSlot, Extended runtime,  
W/O rail kit

SRT10KXLI

## Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V 400 V 3 phase
Product or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V 380 V 415 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	10000 W
rated power in VA	10000 VA
output connection type	6 IEC 60320 C13 3 IEC Jumpers 4 IEC 60320 C19
Output connector type	Hard Wire 3-wire (H N + E) 1
Provided equipment	CD with software Documentation CD Installation guide Temperature Probe USB cable Warranty card Web/SNMP Management Card
Range of Product	Smart-UPS On-Line

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Efficiency	<a href="#">View Efficiency Graph</a> 
Battery Type	Lead-Acid battery
Battery Voltage	+/-192 V (split battery referenced to neutral)
Extendable Run Time	1
Included Battery Modules	0
Typical recharge time	1.5 h

RBC Quantity	2
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC140</a>  <a href="#">SRT192BP2US</a>  <a href="#">SRT192RMBPUS</a> 
Battery Charge Power (Watts)	876 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
Topology	Double Conversion Online

## Physical

color	Black
Height	17.01 in (43.2 cm)
Width	10.35 in (26.3 cm)
Depth	28.15 in (71.5 cm)
Net Weight	246.52 lb(US) (111.82 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

## Input

Efficiency at full load	100...275 V adjustable (half load) 173...476 V adjustable (half load)
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G) 1 Hard Wire 5-wire (3PH + N + G)
Input Frequency	40 - 70 Hz auto-sensing

## Output

Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	10000 VA
Max Configurable Power (Watts)	10000 W
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

<b>Product Certifications</b>	CE EAC IRAM RCM VDE
<b>Marking</b>	CE Mark
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic level</b>	55 dBA
<b>Online Thermal Dissipation</b>	1947 Btu/h
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...50000 ft (0...15240 m)
<b>IP degree of protection</b>	IP20
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 % non-condensing

## Communications & Management

<b>Emergency Power Off (EPO)</b>	Yes
<b>Free slots</b>	1
<b>Pre-Installed SmartSlot™ Cards</b>	Network management card 3 with environmental monitoring
<b>Alarm</b>	Audible and visible alarms : prioritized by severity

## Surge Protection and Filtering

<b>Surge energy rating</b>	480 J
----------------------------	-------

## Ordering and shipping details

<b>GTIN</b>	731304304272
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	18.15 in (46.100 cm)
<b>Package 1 Width</b>	39.37 in (100.000 cm)
<b>Package 1 Length</b>	23.62 in (60.000 cm)
<b>Package weight(Lbs)</b>	279.590 lb(US) (126.820 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **22852**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **409c68a1-39a6-4e5f-b080-12befe783ad8**

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

### Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **User replaceable**

Take-back **Yes**

WEEE Label  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

---



